



Welding light









TABLE OF CONTENTS

Welding light

Welding light product information	page	6
Welding curtains	page	8
Protection curtains	page	11
Welding strips	page	12
Suspension clips & mounting strips	page	13
Accordion folding strip system	page	15
Welding sheet	page	16
Impact plate	page	17

WELDING LIGHT



WELDING LIGHT

The main dangers of unprotected exposure to welding light are: actinic conjunctivitis (during short-term exposure), cataract (by prolonged exposure) and skin burn. The latter can also lead to skin cancer. The welder protects himself by wearing a welding mask and protective clothing but bystanders are exposed to the same dangers. This is why it is important to protect bystanders in the work place to prevent long-term illness.

When protecting the welding area, it is important not to isolate it from other work areas which is one of the reasons why a welding curtain should be made of transparent material. This not only helps to keep an overview of the work progress, but also allows for a quick response in the case of emergencies. It also prevents the welder from suffering from claustrophobia.

CEPRO offers a large range of welding light filtration products which all filter harmful welding light.

Certification

All CEPRO products have been approved according to the European EN ISO 25980 standard and are regularly retested and re-certified. Therefore customers are always assured of obtaining a safe product. The standard establishes requirements with regard to:

- Filtration of harmful ultraviolet (UV) and still visible blue light radiation.
- UV stability. This feature allows an approved CEPRO product to offer long term filtration properties.
- Flame extinction; if a CEPRO curtain catches fire, the material will extinguish automatically after the seat of the fire has been extinguished.

CEPRO products offer protection. They prevent actinic conjunctivitis, cataract, burnt skin, create a safe environment for bystanders and considerably reduce medical costs.

Available colours

CEPRO supplies transparent welding curtains and strips in three different colours: CEPRO Orange-CE, CEPRO Bronze-CE and Cepro Green-6. These colours provide excellent filters against harmful welding light and also offer protection against irritating (not harmful) welding light.

CEPRO also supplies a Green-9 colour. Separations of this material are opaque and extremely suitable for the shielding of several separate welding work areas without causing any nuisance to other welders.

Available products

The CEPRO range includes a large variety of products such as:

- Welding curtains for the shielding of large surfaces.
- Welding strips (2 of 3mm thick) for situations where mechanical load-bearing capacity is required.
- Suspension and mounting parts for mounting strips
- Welding sheets (1mm thick) for larger surfaces.
- Impact plate, a hard impact resistant material made of polycarbonate.

Each of these CEPRO products has been developed for use in specific working conditions for the optimal fit-out of a workplace.











WELDING LIGHT













WELDING LIGHT Welding curtains

CEPRO WELDING CURTAINS 140CM WIDE

- Approved in accordance with EN ISO 25980
- Standard width 140cm
- Fully seamed all-around

- 7 eyelets every on one side measuring 140cm
- Snap-fasteners on both sides
- Including 7 free steel suspension rings

CEPRO ORANGE-CE WELDING CURTAIN 140CM WIDE

H. 160cm x 140cm	16.15.16
H. 180cm x 140cm	16.15.18
H. 200cm x 140cm	16.15.20
H. 220cm x 140cm	16.15.22
H. 240cm x 140cm	16.15.24
H. 260cm x 140cm	16.15.26
H. 280cm x 140cm	16.15.28
H. 300cm x 140cm	16.15.30
Custom-made* < 10m ²	16.15.99
Custom-made* > 10m ²	16.15.99
*For conditions austom made	autoina ana nac

*For conditions custom-made curtains see page page 9

H. 160 cm x 140cm per 10 16.15.16.0010 H. 180 cm x 140cm per 10 16.15.18.0010 H. 200 cm x 140cm per 10 16.15.20.0010

EN ISO 25980 APPROVED





CEPRO GREEN-9 WELDING CURTAIN 140CM WIDE

H. 160cm x 140cm	16.19.16
H. 180cm x 140cm	16.19.18
H. 200cm x 140cm	16.19.20
H. 220cm x 140cm	16.19.22
H. 240cm x 140cm	16.19.24
H. 260cm x 140cm	16.19.26
H. 280cm x 140cm	16.19.28
H. 300cm x 140cm	16.19.30
Custom-made* < 10m ²	16.19.99
Custom-made* > 10m ²	16.19.99
*F	

*For conditions custom-made curtains see page page 9

H. 160 cm x 140cm per 10	16.19.16.0010	box
H. 180 cm x 140cm per 10	16.19.18.0010	box
H. 200 cm x 140cm per 10	16.19.20.0010	box







CEPRO GREEN-6 WELDING CURTAIN 140CM WIDE

H. 160cm x 140cm	16.16.16
H. 180cm x 140cm	16.16.18
H. 200cm x 140cm	16.16.20
H. 220cm x 140cm	16.16.22
H. 240cm x 140cm	16.16.24
H. 260cm x 140cm	16.16.26
H. 280cm x 140cm	16.16.28
H. 300cm x 140cm	16.16.30
Custom-made* < 10m ²	16.16.99
Custom-made* > 10m ²	16.16.99

*For conditions custom-made curtains see page page 9

H. 160 cm x 140cm per 10	16.16.16.0010	box
H. 180 cm x 140cm per 10	16.16.18.0010	box
H. 200 cm x 140cm per 10	16.16.20.0010	box

EN ISO 25980 APPROVED





CEPRO BRONZE-CE WELDING CURTAIN 140CM WIDE

H. 160cm x 140cm	16.17.16
H. 180cm x 140cm	16.17.18
H. 200cm x 140cm	16.17.20
H. 220cm x 140cm	16.17.22
H. 240cm x 140cm	16.17.24
H. 260cm x 140cm	16.17.26
H. 280cm x 140cm	16.17.28
H. 300cm x 140cm	16.17.30
Custom-made* < 10m ²	16.17.99
Custom-made* > 10m ²	16.17.99

*For conditions custom-made curtains see page page 9

H. 160 cm x 140cm per 10	16.17.16.0010	box
H. 180 cm x 140cm per 10	16.17.18.0010	box
H. 200 cm x 140cm per 10	16.17.20.0010	box









CONDITIONS CUSTOM-MADE CURTAINS

- PVC suspension eyelets every 22.5cm
- · 5cm seam all-around
- · Snap-fasteners on both vertical sides
- Minimum size supplied is 1m²
- · Minimum length supplied per side is 100cm
- Due to the elasticity of the PVC material, 2 % tolerance should be taken into account on the measurements provided
- The maximum size per curtain is approx. 24m² (connectable for larger areas)
- · Custom-made curtains are not returnable

CEPRO WELDING CURTAINS 220CM WIDE

- Approved in accordance with EN ISO 25980
- Standard width 220cm
- Fully seamed all-around

- 11 eyelets on one side measuring 220cm
- Snap-fasteners on both sides
- Including free steel suspension rings

CEPRO ORANGE-CE WELDING CURTAIN 220CM WIDE

H. 160cm x 220cm 18.15.16 H. 180cm x 220cm 18.15.18 EN ISO 25980 APPROVED





CEPRO GREEN-9 WELDING CURTAIN 220CM WIDE

H. 160cm x 220cm 18.19.16 H. 180cm x 220cm 18.19.18 EN ISO 25980 APPROVED





CEPRO GREEN-6 WELDING CURTAIN 220CM WIDE

H. 160cm x 220cm 18.16.16 H. 180cm x 220cm 18.16.18 EN ISO 25980 APPROVED





CEPRO BRONZE-CE WELDING CURTAIN 220CM WIDE

H. 160cm x 220cm 18.17.16 H. 180cm x 220cm 18.17.18







WELDING LIGHT Welding curtains

CEPRO WELDING CURTAINS EYELETS ALL AROUND

- Approved in accordance with EN ISO 25980
- Standard heigth 180cm
- Fully seamed all-around

- Suspension eyelets all around
- Including free steel suspension rings

CEPRO ORANGE-CE WELDING CURTAIN 180CM HIGH

H. 180cm x 120cm (6'x4') 14.15.04 H. 180cm x 180cm (6'x6') 14.15.06 H. 180cm x 240cm (6'x8') 14.15.08

EN ISO 25980 APPROVED






CEPRO GREEN-9 WELDING CURTAIN 180CM HIGH

H. 180cm x 120cm (6'x4') 14.19.04 H. 180cm x 180cm (6'x6') 14.19.06 H. 180cm x 240cm (6'x8') 14.19.08

EN ISO 25980 APPROVED





CEPRO GREEN-6 WELDING CURTAIN 180CM HIGH

H. 180cm x 120cm (6'x4') 14.16.04 H. 180cm x 180cm (6'x6') 14.16.06 H. 180cm x 240cm (6'x8') 14.16.08 EN ISO 25980 APPROVED





CEPRO BRONZE-CE WELDING CURTAIN 180CM HIGH

H. 180cm x 120cm (6'x4') 14.17.04 H. 180cm x 180cm (6'x6') 14.17.06 H. 180cm x 240cm (6'x8') 14.17.08





WELDING LIGHT Welding curtains



CEPRO WELDING CURTAINS MIXED COLOURS

- Approved in accordance with EN ISO 25980
- Standard width 150cm
- Seamed at the top and the bottom
- 7 suspension eyelets on the side measuring 150cm
- Snap-fasteners on both sides

- Including 7 free steel suspension rings
- Colour coverage from the bottom to the top: 40cm CEPRO Orange-CE, 120cm CEPRO Green-9, remainder CEPRO Orange-CE.

CEPRO WELDING CURTAIN MIXED COLOURS

H. 160cm x 150cm	19.91.16
H. 180cm x 150cm	19.91.18
H. 200cm x 150cm	19.91.20

EN ISO 25980 APPROVED





CEPRO PROTECTION CURTAINS 140CM WIDE

- CEPRO Yellow only provide protection against exposure to UV radiation
- Standard 140cm wide
- Fully seamed all-around

- 7 eyelets every on one side measuring 140cm
- Snap-fasteners on both sides
- Including 7 free steel suspension rings

CEPRO YELLOW UV-CURTAIN 140CM WIDE

H. 160cm x 140cm	16.11.16
H. 180cm x 140cm	16.11.18
H. 200cm x 140cm	16.11.20



CEPRO GRINDING CURTAIN 140CM WIDE - B2 QUALITY

H. 160cm x 140cm	16.10.16
H. 180cm x 140cm	16.10.18
H. 200cm x 140cm	16.10.20
H. 220cm x 140cm	16.10.22
H. 240cm x 140cm	16.10.24
H. 260cm x 140cm	16.10.26
H. 280cm x 140cm	16.10.28
H. 300cm x 140cm	16.10.30
Custom-made < 10m ²	16.10.99
Custom-made > 10m ²	16.10.99

DIN 4102 - B2 APPROVED



CEPRO GRINDING CURTAIN 140CM WIDE - B1 QUALITY

H. 160cm x 140cm	16.30.16
H. 180cm x 140cm	16.30.18
H. 200cm x 140cm	16.30.20
H. 220cm x 140cm	16.30.22
H. 240cm x 140cm	16.30.24
H. 260cm x 140cm	16.30.26
H. 280cm x 140cm	16.30.28
H. 300cm x 140cm	16.30.30
Custom-made < 10m ²	16.30.99
Custom-made > 10m ²	16.30.99

DIN 4102 - B1 APPROVED





WELDING LIGHT Welding strips

CEPRO WELDING STRIPS

- Approved in accordance with EN ISO 25980
- Standard 300mm wide
- 2mm and 3mm thickness

- Full roll 50 meters
- Available cut and punched
- Plastic suspension clips

CEPRO ORANGE-CE WELDING STRIPS

300 x 2mm uncut per meter	26.25.02
300 x 3mm uncut per meter	26.25.03
300 x 2mm uncut per full roll	26.25.02.0050
300 x 3mm uncut per full roll	26.25.03.0050

300 x 2mm cut to size and punched 26.25.02.91 according to the CEPRO pattern minimum length 150cm 300 x 3mm cut to size and punched 26.25.03.91 according to the CEPRO pattern minimum length 150cm

EN ISO 25980 APPROVED





CEPRO GREEN-9 WELDING STRIPS

300 x 2mm uncut per meter	26.29.02
300 x 3mm uncut per meter	26.29.03
300 x 2mm uncut per full roll	26.29.02.0050
300 x 3mm uncut per full roll	26.29.03.0050

300 x 2mm cut to size and punched 26.29.02.91 according to the CEPRO pattern minimum length 150cm 300 x 3mm cut to size and punched 26.29.03.91 according to the CEPRO pattern minimum length 150cm

EN ISO 25980 APPROVED





CEPRO GREEN-6 WELDING STRIPS

300 x 2mm uncut per meter	26.26.02
300 x 2mm uncut per full roll	26.26.02.0050

300 x 2mm cut to size and punched 26.26.02.91 according to the CEPRO pattern minimum length 150cm

EN ISO 25980 APPROVED





CEPRO BRONZE-CE WELDING STRIPS

 300 x 2mm uncut per meter
 26.27.02

 300 x 2mm uncut per full roll
 26.27.02.0050

300 x 2mm cut to size and punched 26.27.02.91 according to the CEPRO pattern minimum length 150cm






WELDING LIGHTSuspension clips for strips

LEADING IN WELDING SAFETY



- Easy assembly of welding strips on a tube Ø 33.7mm
- Suitable for overlap of 5 and 10cm
- Easy to open and close on the folding line




CEPRO STANDARD SUSPENSION CLIP 20CM

Standard clip 20cm

20.11.01





10 cm / 66% overlap (2 holes overlap)


CEPRO SQUARE SUSPENSION CLIP 10CM

Square clip 10cm

20.11.09

Suspension clip to be used as initial clip in a separation or next to a support.





10 cm / 66% overlap (2 holes overlap)

CEPRO FILLING PIECE 5CM

Filling piece 5cm

20.11.90

Filling piece, for overlap of 5cm or next to a support in combination with a square clip.








WELDING LIGHT Mounting welding strips

■ 10cm / 66% overlap (2 holes overlap)



► 5cm / 33% overlap (1 hole overlap)



Open the clip on the folding line.




Press the clip onto the tube.




Push the bolts through both of the round holes in the middle of the clip.




A Slide the overlapping strips over the bolts. Alternately assemble the strips concavely and convexly. For a 10cm overlap use both pre-punched holes and for a 5cm overlap only use the outer holes.



5 Close the clips and tighten the nuts and bolts.



6 If you have used a 5cm overlap then you can use the filling pieces in the openings between the clips.



Calculation diagram for strip separations with an overlap of 100 mm (66%)

Widht separation (mm)	900	1100	1300	1500	1700	1900	2100	2300	2500	2700	2900	3100	3300	3500	3700	3900	4100	4300	4500	4700	4900	5100	5300	2200	2200	2900	6100	9300	6500
Number strips	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32
Number standard clips	3	4	5	6	7	7	8	9	10	11	12	12	13	14	15	16	16	17	18	19	20	20	21	22	23	24	24	25	26
Number square clips	2	2	2	2	2	3	3	3	3	3	3	4	4	4	4	4	5	5	5	5	5	6	6	6	6	6	7	7	7
Number filling pieces	2	2	2	2	2	4	4	4	4	4	4	6	6	6	6	6	8	8	8	8	8	10	10	10	10	10	12	12	12

Calculation diagram for strip separations with an overlap of 50 mm (33%)

Widht separation (mm)	800	1050	1300	1550	1800	2050	2300	2550	2800	3020	3300	3550	3800	4050	4300	4550	4800	5050	5300	5550	5800	6050	6300	6550	9	7050	7300	7550	7800
Number strips	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31
Number standard clips	2	3	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30
Number square clips	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2	2
Number fillling pieces	4	5	6	7	8	9	10	11	12	13	14	15	16	17	18	19	20	21	22	23	24	25	26	27	28	29	30	31	32



CEPRO ACCORDION FOLDING STRIP SYSTEM

- Minimum amount of space
- Easy to operate
- Flexible in dividing the workspace



CEPRO SUSPENSION FOLDING STRIP SYSTEM

Complete mounting set for folding strips system, per running meter. Including all supports for mounting the system under a ceiling.

Cepro folding strip mounting system 20.95.95


Minimum width : 130cm Maximum width : 1.000cm



CEPRO STRIPS FOLDING STRIP SYSTEM

Complete strip set for accordion folding strip system per square meter. Thickness strips 2mm. Maximum strip height 350cm.


Cepro Orange-CE folding strip 300x2 mm system	27.55.32.10
Cepro Green-9 folding strip 300x2 mm system	27.59.32.10
Cepro Bronze-CE folding strip 300x2 mm system	27.57.32.10
Cepro Green-6 folding strip 300x2 mm system	27.56.32.10



CEPRO STRIPS FOLDING STRIP SYSTEM

Complete strip set for accordion folding strip system per square meter. Thickness strips 3mm. Maximum strip height 250cm.

Cepro Orange-CE folding strip 300x3 mm system	27.55.33.10
Cepro Green-9 folding strip 300x3 mm system	27.59.33.10





WELDING LIGHT Welding sheet 1mm

CEPRO WELDING SHEET 1MM

- Approved in accordance with EN ISO 25980
- Standard 570mm wide
- 1mm thickness
- Full roll 50 meters

- 4 eyelets every on one side measuring 570mm
- Metal suspension rings included
- Packed 4 per box, working width per box 2 meters
- Supplied rolled in paper

CEPRO ORANGE-CE WELDING SHEET 1MM

570 x 1mm, roll 50 meter length 22.15.01

Working width per box 200 cm.

570 x 1 x 1.600mm, per 4 pieces	22.15.16.0004
570 x 1 x 1.800mm, per 4 pieces	22.15.18.0004
570 x 1 x 2.000mm, per 4 pieces	22.15.20.0004
570 x 1 x 2.200mm, per 4 pieces	22.15.22.0004

EN ISO 25980 APPROVED





CEPRO GREEN-9 WELDING SHEET 1MM

570 x 1mm, roll 50 meter length 22.19.01

Working width per box 200 cm.

570 x 1 x 1.600mm, per 4 pieces	22.19.16.0004
570 x 1 x 1.800mm, per 4 pieces	22.19.18.0004
570 x 1 x 2.000mm, per 4 pieces	22.19.20.0004
570 x 1 x 2.200mm, per 4 pieces	22.19.22.0004

EN ISO 25980 APPROVED





CEPRO GREEN-6 WELDING SHEET 1MM

570 x 1mm, roll 50 meter length 22.16.01

Working width per box 200 cm.

Working Water per box 200 cm.	
570 x 1 x 1.600mm, per 4 pieces	22.16.16.0004
570 x 1 x 1.800mm, per 4 pieces	22.16.18.0004
570 x 1 x 2.000mm, per 4 pieces	22.16.20.0004
570 x 1 x 2.200mm, per 4 pieces	22.16.22.0004

EN ISO 25980 APPROVED





CEPRO BRONZE-CE WELDING SHEET 1MM

570 x 1mm, roll 50 meter length 22.17.01

Working width per box 200 cm.

570 x 1 x 1.600mm, per 4 pieces	22.17.16.0004
570 x 1 x 1.800mm, per 4 pieces	22.17.18.0004
570 x 1 x 2.000mm, per 4 pieces	22.17.20.0004
570 x 1 x 2.200mm, per 4 pieces	22.17.22.0004







CEPRO IMPACT PLATE 3MM

- Approved in accordance with EN ISO 25980
- Hard impact resistant material
- 3mm thickness

- Polycarbonate
- Available in custom measurements

CEPRO IMPACT BRONZE

2050 x 1250mm, thickness 3mm 28.27.01 1025 x 1250mm, thickness 3mm 28.27.05

Impact cut to size 20.95.28.0001

EN ISO 25980 APPROVED





CEPRO IMPACT GREEN

2050 x 1250mm, thickness 3mm 28.29.01 1025 x 1250mm, thickness 3mm 28.29.05

Impact cut to size 20.95.28.0001

EN ISO 25980 APPROVED





CONDITIONS CUSTOM-CUT IMPACT

- Minimum calculated dimension 0,25m²
- Minimum length calculated is 50cm
- · Custom cut Impact is not returnable



CEPRO IMPACT PLATE SPECIALS



CEPRO Impact material is also available in the colour Clear.

For more information, feel free to ask our sales department for a quotation.



CEPRO International B.V.

Postal adress: Parallelweg 38 5121 LD Rijen, Netherlands

Visiting adress:
Parallelweg 38
5121 LD Rijen, Netherlands

Warehouse adress: Parallelweg 40 5121 LD Rijen, Netherlands



Protecting people

We protect people and the surrounding area from danger by setting up safe welding and grinding sites.

Solid operational management also means working to protect your employees and the surrounding area from danger. At CEPRO, we believe sharing knowledge about legal safety requirements forms the cornerstone of a productive business relationships and long-term partnership.

Reliable quality and service in safety

This allows us to combine all the knowledge and expertise found in today's sector in our products, services and processes. We treat every request with due care and attention and work to tailor our solutions to the individual requirements of the client or end user. And throughout, we leave nothing to chance. Working together with our client, and together with our partners. We believe that continuously investing in knowledge, training and relationships is the best guarantee for consistent and dependable quality and solid service in safety that complies with international regulations. It's what has made CEPRO the global market leader in its sector.

Happy in your job

When it comes to safety and job satisfaction, only the best is good enough for our own people too. After all, whether or not you are happy in your job depends to a large extent on how secure and satisfied you feel as an employee. When our employees feel happy, this contributes to their personal health and productivity. And this in turn has a positive impact on customer satisfaction.

www.cepro.eu



WELDONE srl + T. +39 0374 948008 + info@weldone.it + www.weldone.it